


ORIENTI UP/DOWN

CE  IP54



CODE*	⊕		☑**		⚡			L x B x D (mm)
	⊕	↷	☑	☑	P	U	CLASS	
0021 01 x	6 x power LED	20°	ALG	GC	14w	24Vdc	⊕	-
0021 01 x t	6 x power LED	40°	ALG	GC	14w	230Vac	⬇	-
0021 02 x	6 x power LED	20°	ALG	GC	14w	24Vdc	⊕	-
0021 02 x t	6 x power LED	40°	ALG	GC	14w	230Vac	⬇	-
0021 05 x	6 x power LED	20°	ALG/C	GC	14w	24Vdc	⊕	-
0021 05 x t	6 x power LED	40°	ALG/C	GC	14w	230Vac	⬇	-
0021 06 x	6 x power LED	20°	ALG/C	GC	14w	24Vdc	⊕	-
0021 06 x t	6 x power LED	40°	ALG/C	GC	14w	230Vac	⬇	-

EN Dimmodule: scheme 2 page 46, Power supply: page 42
Controllors rgb: scheme 2.

FR Module dimmable: schéma 2 page 46, Alimentation: page 42
Contrôleurs rvb: schéma 2.

NL Dimmodule: schema 2 op pagina 46, Voeding: pagina 42
Kleursturing: schema 2.

** see / voir / zie p. 4

